

Optimizing Remedial Strategies in Brazil:

An Evaluation of Dual Thermal Treatment Technologies Using Dynamic Cost Modeling



Miles Ingraham, PE, PG

(207) 701-6544

Miles.Ingraham@Jacobs.com

Co-Authors


James Arthur, PG - Jacobs

Paulo de Sá Rego – Worley Consulting

Laís Muchatte Trento – Worley Consulting

Agenda

- Site Overview and Remedial Strategy
- Cost Estimation: 101
- Multi-Variate Cost Estimation
 - Secondary Source Determination and Remedial Targets
 - Technical Considerations for Dual Thermal Technologies
 - Dynamic Cost Modeling Using Multi-Variate Cost Estimation
- Key takeaways



Site Overview



- Inactive site located in **northeastern Brazil**
- Solid and liquid wastes composed of **chlorobenzenes, chloronitrobenzenes, chloroanilines, and BTEX**
- Vadose zone and saturated zones to be remediated sequentially to **address secondary sources**


Remedial Strategy

- Seven former units being investigated, **two are fully investigated and ready for remediation**
- Remedy technologies split into **vadose and saturated zones**
- Need to understand cost of vadose zone remediation to aid in **technology selection, optimize cost-performance outcomes, and book reserve**
- Remediation goals include cleanup, but also use of **sustainable and novel technologies (i.e., limit or eliminate offsite disposal)**



CSM Overview

- Complex mixture of organochlorinated compounds
- Residual free phase product present



Cost Estimation: 101




Cost Estimation Basics – Classification Matrix

	Primary Characteristic	Secondary Characteristic			
ESTIMATE CLASS	MATURITY LEVEL OF PROJECT DEFINITION DELIVERABLES Expressed as % of complete definition	END USAGE Typical purpose of estimate	METHODOLOGY Typical estimating method	EXPECTED ACCURACY RANGE Typical +/- range relative to index of 1 (i.e. Class 1 estimate) ^[a]	PREPARATION EFFORT Typical degree of effort relative to least cost index of 1 ^[b]
Class 5	0% to 2%	Screening or feasibility	Stochastic (factors and/or models) or judgment	4 to 20	1
Class 4	1% to 15%	Concept study or feasibility	Primarily stochastic	3 to 12	2 to 4
Class 3	10% to 40%	Budget authorization or control	Mixed but primarily stochastic	2 to 6	3 to 10
Class 2	30% to 75%	Control or bid/tender	Primarily deterministic	1 to 3	5 to 20
Class 1	65% to 100%	Check estimate or bid/tender	Deterministic	1	10 to 100

Cost Estimation Basics – Accuracy Range

- Important for understanding certainty and potential cost swings
 - Certainty increases as project scope defined
- Estimates tend to skew higher than true end cost



Remedial Strategy, Technology Evaluation, & Cost Estimation



Remedial Options Evaluation (Class 5)


Criteria	Alt 1 Containment/ Capping	Alt 2a Excavation, Offsite Disposal Landfill	Alt 2b Excavation, Offsite Disposal Incinerator	Alt 3a Excavation, ESTD	Alt 3b Excavation, ESS	Alt 4 ISTD (Deep), Excavation, ESS (Shallow)
Effectiveness						
Implementability						
Sustainability						
Cost (Class 5)	\$	\$	\$\$\$\$	\$\$\$	\$\$	\$\$
Overall Evaluation						

-  Low - Approach expected to perform poorly against criterion when compared to other approaches
-  Moderate - Approach is expected to perform moderately well against criterion when compared with other approaches
-  High - Approach is expected to perform very well against criterion when compared with other approaches


Technology Overview

- In situ thermal desorption (ISTD)
 - Install electric heater wells, vapor recovery system, and monitoring network
 - Condense vapors, treat, dispose
- Ex situ smoldering (ESS)
 - Excavate vadose zone soil, stockpile
 - Mix soil with carbon, concrete
 - Load box, treat soil and process vapor
 - Remove treated soil, backfill

ISTD Concept



Smoldering Concept





Establishing the Remedial Targets

- Cleanup levels for most site COIs not established
 - Rather, legislation calls for “addressing secondary sources”
 - Secondary source = mass contributing to secondary media


So what are we targeting?

Establishing the Remedial Targets


- ✓ Step 1 – Assess NAPL saturation (NAPLt) for each sample
- ✓ Step 2 – Assess leachability of COIs from subset of samples
- ✓ Step 3 – Perform multi-variate statistical analysis correlating NAPL saturation and leachability
- ✓ Step 4 – Reference leachability to site risk values (CMAs) and screen exceedances




Establishing the Remedial Targets




Dynamic Cost Model - Multivariate Cost Estimate



Example Estimate Output



Remedial Technology Cost Functions



Key Takeaways

- Dynamic cost modeling can help decision making when multiple technical options available
 - Can even steer specific ways in which technology is applied
- Sometimes additional data and analysis are warranted, even after Class 5 estimate
 - Conclusions under Class 5 can differentiate from Class 3
- Remediation technologies not always “\$/volume”, but scale differently

Optimizing Remedial Strategies in Brazil:

An Evaluation of Dual Thermal Treatment Technologies Using Dynamic Cost Modeling



Miles Ingraham, PE, PG

(207) 701-6544

Miles.Ingraham@Jacobs.com



Co-Authors

James Arthur, PG - Jacobs

Paulo de Sá Rego – Worley Consulting

Laís Muchatte Trento – Worley Consulting



Challenging today.
Reinventing tomorrow.



Copyright notice

Important

© Copyright Jacobs Group 2024 . All rights reserved. The content and information contained in this presentation are the property of the Jacobs Group of companies ("Jacobs Group"). Publication, distribution, or reproduction of this presentation in whole or in part without the written permission of Jacobs Group constitutes an infringement of copyright. Jacobs, the Jacobs logo, and all other Jacobs Group trademarks are the property of Jacobs Group.

NOTICE: This presentation has been prepared exclusively for the use and benefit of Jacobs Group client. Jacobs Group accepts no liability or responsibility for any use or reliance upon this presentation by any third party.