

Optimizing Long-Term Vapor Intrusion Monitoring During Site Management

Battelle Chlorinated Conference, Denver, Colorado
June 2-6, 2024

Gwen Buckley (Jacobs)

Keri Hallberg P.E., Adrienne Jones, Loren Lund Ph.D. (Jacobs)

Agenda

- Introduction and Objective
- Site Background
 - VI LTM Program
- Lines of Evidence Considered
- Data Evaluation
- Data Evaluation Summary
- VI LTM Optimization Summary
- Questions and Answers

Introduction and Objective

- Long-term monitoring (LTM) for vapor intrusion (VI) can be expensive, intrusive, and potentially unnecessary

Objective

Summarize an effective VI LTM optimization strategy using a case study site with chlorinated volatile organic compound (cVOC) data collected from 2009 to 2021

Site Background

- Coastal industrial site
- Small and large occupied and unoccupied buildings
- Historical machine, vehicle, locomotive, and electrical maintenance, and munitions loading
- Documented trichloroethene (TCE) use and ground-surface disposal
- Current use: Storage and maintenance
- Future anticipated use: Industrial



Site Background (continued)

- Site-related chemicals of concern (COCs):
 - TCE
 - Cis-1,2-dichloroethane (DCE)
 - 1,1-DCE
 - Vinyl chloride (VC)
- Site remedy:
 - *In situ* chemical reduction (ISCR) through zero-valent iron injections where TCE > 1,000 µg/L
 - Enhanced reductive dechlorination (ERD) through emulsified vegetable oil injections where TCE < 1,000 µg/L
 - Land use controls (LUCs)



VI LTM Program

- 2009 VI investigation indicated no current or future risk
- **But wait!** GW remedial action (RA) could increase concentrations of COC degradation products or explosive hazards
- VI LTM used to monitor building use/condition and changes in concentrations of constituents of interest (COIs)

Inhalation risk COIs:

- TCE, VC, *cis*-1,2-DCE
- Degradation products: 1,1-DCE, *trans*-1,2-DCE, 1,2-dichloroethane (DCA)

Explosive hazard COIs:

- Hydrogen sulfide*, methane

*ERD by-product

VI LTM Program (continued)



- Semi-annual
- Types of VI data collected were determined by review of LTM GW data
- Updated building surveys
- If warranted: Collected indoor air (IA), outdoor air (OA), and subslab soil gas (SG) at occupied buildings
- Post-injection: Monitored SG and IA explosive hazards at all buildings for at least 3 rounds


Lines of Evidence Considered

- Remedial Action-Construction Phase
 - Initial ISCR and ERD injections site-wide
- Remedial Action-Operation (RA-O) Phase
 - Site/LUC inspections
 - Five-Year Reviews (FYR)
 - Groundwater and stormwater monitoring (16 events)
 - Additional targeted ERD injections (2 events)
 - Building surveys and inhalation/explosive risk COI monitoring (16 events)
 - Follow-on VI investigations triggered at two buildings proposed for occupancy

Data available from
2009 to 2021

Data continually reviewed
for optimization
opportunities

Data Evaluation – Surveys




- **B, C, E, and F (2012-2020)** – B and E proposed for occupancy, resulting in follow-on VI risk investigations
- **A (2012-2014)** – Structure fell into disrepair and became unoccupiable
- **D (2012)** – VI LUC boundary redefined based on GW data

Optimization Opportunities!

- ✓ Building A VI LTM discontinued after building vacated
- ✓ Building D removed from VI LTM since it was no longer within VI LUC boundary

Data Evaluation – Follow-On VI Risk Investigations



- **Building B:**
 - IA and SG COI concentrations < screening criteria
 - No current risk, but potential future risk from ongoing RA monitored
- **Building E:**
 - IA and SG COI concentrations < screening criteria
 - Building located upgradient of GW plume
 - Occupants moved out
 - No current or future risk

Optimization opportunity!

- ✓ Building E VI LTM discontinued after building vacated and since no VI risk

Data Evaluation – Explosive Hazard Monitoring

- Collected baseline SG and IA explosive COI data from all buildings
- Post-injection (when short-term SG increases expected):
 - Collected at least 3 rounds of data
 - Compared to project action limits (PALs)
 - If > PAL, continued monitoring until 3 consecutive rounds < PAL
 - If < PAL, discontinued monitoring until next treatment (as necessary)

Explosive Hazard PAL	
Hydrogen Sulfide	0.4 percent
Methane	0.5 percent

PAL conservatively established as 1/10th the lower explosive limit (LEL)

Overall finding:
No explosive hazards during RA. Monitor again if additional treatment implemented.

Data Evaluation – Trend Analyses



- Reviewed SG data to determine COIs for trend analysis (excluded non-detects)
- TCE and VC trends evaluated for Bldgs A, B, and F
- Plotted available GW data (within 100 feet of bldg) and IA data
 - *Trend analysis results for Building A used in subsequent slides as being representative*



Data Evaluation – GW Trends

TCE Highlights:

- ✓ Concentration and spatial distribution significantly reduced through RA
- ✓ Plumes flowing away from bldgs
- ✓ Future concentrations not expected to result in VI risk




VC Highlights:

- ✓ Similar/fluctuating spatial & temporal distribution post-injections
- ✓ Trends related to TCE degradation



Data Evaluation – Building A GW and IA Trend (TCE)




Highlights:

- ✓ IA < VISL
- ✓ No VI (at max or any GW TCE level)
- ✓ Significant TCE GW decline
- ✓ GW unlikely to increase > maximum

Optimization Opportunities!

- Sample IA only if GW > maximum
- Notify using cumulative rather than individual COI risk exceedance
- Recommended discontinuing all VI monitoring

Data Evaluation – Building A GW and IA Trend (VC)



Highlights:

- ✓ IA < VISL
- ✓ No VI (at max or any GW VC level)
- ✓ Transient GW increases post-injection
- ✓ Future TCE degradation not expected to increase VC

Optimization Opportunities!

- Sample IA only if GW > maximum
- Notify using cumulative rather than individual COI risk exceedances
- Recommended discontinuing all VI monitoring

Data Evaluation Summary

- No VI (IA < VISLs), even after RA injections (12 yrs of LTM)
- RA injections significantly reduced GW concentrations
 - Remaining low-level TCE flowing away from occupied buildings
- Transient VC increases due to injections
 - Future TCE degradation not expected to further increase VC
- No future VI expected
- No explosive hazards from RA

VI LTM Optimization Summary

- ✓ Leveraged ongoing LTM data review to reduce sampling/number of buildings
 - Optimized GW triggers (e.g., compared with max) for VI sampling (IA/OA/SG)
 - Discontinued VI sampling if building became unoccupied
 - Removed building as GW VI LUC boundary changed
- ✓ Changed notification trigger from individual COI to cumulative risk targets
- ✓ Recommended discontinuing VI LTM since no VI risks based on 12 yrs LTM data

Benefits

- ✓ Minimizes data collection/costs
- ✓ Provides data-driven exit strategy to discontinue VI LTM

Thank you!

gwen.buckley@jacobs.com



Challenging today.
Reinventing tomorrow.



Copyright notice

Important

© Copyright Jacobs Group 2024 . All rights reserved. The content and information contained in this presentation are the property of the Jacobs Group of companies ("Jacobs Group"). Publication, distribution, or reproduction of this presentation in whole or in part without the written permission of Jacobs Group constitutes an infringement of copyright. Jacobs, the Jacobs logo, and all other Jacobs Group trademarks are the property of Jacobs Group.

NOTICE: This presentation has been prepared exclusively for the use and benefit of Jacobs Group client. Jacobs Group accepts no liability or responsibility for any use or reliance upon this presentation by any third party.